



Söderköping March 12, 2020

Maintenance procedure for HTC Superfloor™

Daily machine cleaning

Dry mop the floor. Fill the tank of the auto scrubber (scrubber dryer) with clean water and mount a 3000 grit diamond impregnated cleaning pad on the pad holder (ensure proper function of the machine prior to scrubbing).

Machine clean the floor at a speed of 3-5 km/h (2-3,5 mph) After cleaning – rinse the pad thoroughly and check if the color is gone. When the color is gone, replace the diamond impregnated cleaning pad with a new one. For extra high gloss, use a high speed burnisher (>1500 RPM) with a clean and dry 3000 grit diamond impregnated cleaning pad.

If the floor is heavily soiled or has spills of oil, add a low-alkaline soap (for example Twister Floor Conditioner or Consolideck DailyKlean) in the auto scrubber. Follow the dosing instructions. Do not use acidic or highly alkaline cleaners as they break down the concrete.

Daily cleaning without machine

Dry mop the floor. Mop with hot water and HTC Cleaner using a cotton mop. Rinse and repeat as needed until water removed from the floor appears to be clean. Use a high speed burnisher (>1500 rpm) with a clean and dry 3000 grit diamond impregnated cleaning pad.

Department of Floor Solutions
HTC Sweden AB